



Crop Lifter / Conditioner



MODELS

CLC-16.....	Six 30" rows
CLC-18.....	Six 36" rows
CLC-19.....	Six 38" rows
	(Eight 30" rows with modifications)

SPECIFICATIONS

	CLC-16	CLC-18	CLC-19
Length	94-5/8"	94-5/8"	94-5/8"
Header Width	182-3/8"	208-1/4"	225-1/4"
Overall width	210"	240-3/4"	252-7/8"
Height	67-5/16"	67-5/16"	67-5/16"
Weight		3,037 lbs.	3,148 lbs.
Pickup	6-Bar Spring Tooth		
Hitch Type	CAT III, CAT IIIN (Optional CAT II)		
Drive	Hydraulic Drive "10 GPM required"		
Gauge Wheel Tires	4-Ply 23x10.5x12		

INDUSTRY LEADER • PROVEN PERFORMANCE • INNOVATIVE DESIGN

1100 Holland Road / Suffolk, VA 23434
Telephone (757) 539-0231 / Fax (757) 934-3264

www.amadas.com

1701 S. Slappey Blvd. / Albany, GA 31701
Telephone (229) 439-2217 / Fax (229) 439-9343

E-mail Address: sales@amadas.com

AMADAS INDUSTRIES whose policy is one of continuous improvement, reserves the right to change specifications design or price without incurring obligation.



Crop Lifter / Conditioner



In keeping with our philosophy of providing farmers with a complete harvesting system, the innovative Amadas Models CLC-18 and CLC-19 Crop Lifter Conditioners bring a completely new concept to lifting and conditioning peanuts and other crops.

- The gentle action of our advanced design allows the windrows to be lifted and replaced without destroying the windrow, reducing the losses from this action!
- Infinitely adjustable hydraulic drive allows exact match of pickup speed to ground speed and eliminates PTO driveline maintenance and problems!
- Low profile design minimizes the distance the plants fall back to the ground thereby reducing losses!
- Reduces dirt, rocks, and other foreign material entering combines improving the operating efficiency of the combines, increasing dryer efficiency, and improving grades!
- Breaking the ground moisture seal promotes uniform drying in the windrow and allows the harvesting operation to begin earlier in the day!
- Utilizes the same advanced six bar pickup, rods, and roller design as our new eight row self-propelled combine headers and has many interchangeable parts with these headers!
- Maintenance is simplified by the open pickup design and easy access plates to drive components!
- Can be adapted for 30" row peanuts!