

## In-Field Crop Transporter



The Amadas In-Field Crop Transporter is the largest available and is designed and built specifically to handle the high capacity output of both the Amadas Pull-Type and the Amadas Self-Propelled combines, including the OCS (Off-Load Conveying System) models.

- Over 1,100 cubic feet of transport capacity - from 20% to 47% more than other dump carts! The Amadas ICT1100 will easily handle two full loads from large volume 7,500 lb. baskets which are standard on high capacity combines!
- Unique hydraulic lift/dump technology features an innovative articulated linkage which provides more rigidity, control and stability while dumping!
- With a dump height in excess of 15 feet, the Amadas ICT1100 provides quick and efficient loading of semi-trailers or large dryer wagons!
- Available with standard 1/4"x3" slot screens for peanuts, 1/8"x3" slot screens for edible beans, or with a small grain option (1/4"x3" slot screens on dump side only, with optional removable liner kit for slots, and all other sides solid).
- Extra large dirt screens - more than double the cleaning capacity of competitive dump carts.
- Additional two stage dirt trap on dump side for added dirt extraction.



# In-Field Crop Transporter



## MODELS

- ICT1100.....Standard Peanut with 1/4" x 3" slots
- ICT1100A.....Edible Bean with 1/8" x 3" slots
- ICT1100B...Convertible Peanut/Small Grain with 1/4" x 3" slots on dump side only

## SPECIFICATIONS

Struck Capacity (ft <sup>3</sup> )	1,100
Grain capacity (lb)	25,000
Cleaning area open for dirt extraction (ft <sup>2</sup> )	(ICT1100) 129 (ICT1100A) 64.5 (ICT1100B) 51.6
Dumping capacity (lb)	30,800
Shipping weight (lb) (without water in tires)	18,040
Dumping angle	46°
Standard wheel size	30.5 x 32
Standard tires	30.5 x 32 16 ply
Box length	15'6"
Loading height	8'6"
Wheel base outside/outside	159"
Min dump height	11'10"
Max dump height	15'
Lift cylinders	4" x 48"
Dump cylinders	4.5" x 72"
Recommended hyd. fluid flow	15 GPM
Volume required to operate	7.6 gal
Min reservoir capacity	15 gal
Dump cycle	<1 min
Reversible tongue	No (special order only)
Dirt lip	2 stage
Access ladder	Exterior and interior
Lights	Light kit to ASAE standard
Hitch	Pin (adj. position) with swivel

**INDUSTRY LEADER • PROVEN PERFORMANCE • INNOVATIVE DESIGN**

1100 Holland Road / Suffolk, VA 23434  
Telephone (757) 539-0231 / Fax (757) 934-3264

[www.amadas.com](http://www.amadas.com)

email Address: [sales@amadas.com](mailto:sales@amadas.com)

1701 S. Slappey Blvd. / Albany, GA 31701  
Telephone (229) 439-2217 / Fax (229) 439-9343

AMADAS INDUSTRIES whose policy is one of continuous improvement, reserves the right to change specifications design or price without incurring obligation.