



Round Module Handler



RMH1000 Base Unit & RMH1010 Mast Unit

Stronger...More Features!

The machine with all the features needed by growers
and *built* to *last*!

- **Stronger - 10,000 lb Lift Capacity**
- **Heavier Construction**
- **Side Shift Forks**
- **Tilting Mast**
- **Low Maintenance**
- **Fits CAT III, IVN, and IV Hitches**

AMERICAN MANUFACTURED • ADVANCED DESIGN • ABSOLUTE SERVICE



RMH1000 & RMH1010 Round Module Handler



Innovative, trouble free design for fork travel: Each fork is supported and its movement controlled by four rollers with hardened, greasable steel bushings on 6" x 6" square tubing lower arm and by long wearing Delrin guides on 4" x 6" rectangular tubing upper arm, eliminating need for telescoping tubes, contamination of exposed greased surfaces by dirt and trash and potential tube misalignment.

Extra heavy duty fork construction: Forks are fabricated with 8" x 8" heavy wall square tubing, steel plate and round tubing. The angled inside portion of the forks has multiple internal support braces for additional strength. Critical connections between forks and frame are reinforced with heavy duty steel plate gussets.

Angled bottom inside portion of fork: Ground and truck bed contact is reduced, allowing smoother pickup and release of module.

Side shift on RMH1000 base unit: Side shift allows simple, precise placement of module for staging or loading of trucks.

Tilt feature on RMH1010 mast unit: The tilt feature allows modules to be easily positioned and released from forks eliminating damage to truck or module. Tilt cylinders also have accumulators for shock absorption reducing stress on forks, frames, and tractor in rough field conditions.

Heavy duty, low maintenance mast design: Mast is constructed of 4" x 6" steel tubing and guided by four, sealed for life, external cam follower bearings. The bearings are easily accessible. No disassembly of the mast is required in the event the bearings need to be replaced. There are no chains to grease or tension and no exposed greased surfaces to attract dirt and trash.

Specifications: RMH1000 Base Unit and RMH1010 Mast Unit

Lifting capacity	10,000 lb.	Shipping Weight - Base RMH1000	2,750 lbs
Height - Base Only	69" (91" to lights)	Shipping Weight - Mast RMH1010	2,100 lbs
Height - with Mast	100"	Shipping Weight - Combined units	4,850 lbs
Width - Base Only (forks closed)	64"	Lift Height - Base Only	24"
Width - with Mast (forks closed)	91"	Lift Height - with Mast	66"
Width - Base Only (forks open)	114"	Lift cylinders	3.5" x 48"
Width - with Mast (forks open)	114"	Fork cylinders	3.5" x 26"
Inside clearance - forks closed	30"	Tilt cylinders	3" x 10"
Inside clearance - forks open	80"	Hitch	CAT III, IVN or IV
Length - Base Only	129"	Lights	2 halogen work lights
Length - with Mast	136"		

INDUSTRY LEADER • PROVEN PERFORMANCE • INNOVATIVE DESIGN

1100 Holland Road / Suffolk, VA 23434

www.amadas.com

1701 S. Slappey Blvd. / Albany, GA 31701

Telephone (757) 539-0231 / Fax (757) 934-3264

email Address: sales@amadas.com

Telephone (229) 439-2217 / Fax (229) 439-9343

AMADAS INDUSTRIES whose policy is one of continuous improvement, reserves the right to change specifications design or price without incurring obligation.